

View Online at <https://aerobasegroup.com/nsn/5340-01-509-7625>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.050 inches

**Second Leg Length:**

2.050 inches

**Furnished Items (non-core):**

2 captive screws, low profile

**Second Leg Width:**

5.380 inches

**First Leg Hole Diameter:**

Between 0.154 inches and 0.157 inches

**Second Leg Hole Diameter:**

Between 0.154 inches and 0.159 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.950 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.090 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

1.425 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.155 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**Center Section Height:**

2.950 inches

**Center Section Width:**

5.380 inches

**Center Section Thickness:**

0.125 inches

**First Leg Width:**

5.380 inches

**First Leg Corner Radius:**

0.060 inches

**First Leg Distance Between Hole Centers Along Width:**

2.950 inches

**First Leg Distance Between Hole Centers Along Length:**

1.090 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.375 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.155 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Product Name:**

Bracket, mounting, 1553 bus coupler

**Material:**

Aluminum alloy 5052

**Material Specification:**

Astm b209, temper h32 assn standard single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 1a military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.