

View Online at <https://aerobasegroup.com/nsn/5340-01-509-7651>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

1.500 inches

Second Leg Width:

9.000 inches

Second Leg End Width:

8.500 inches

First Leg Hole Diameter:

Between 0.264 inches and 0.271 inches

Second Leg Hole Diameter:

Between 0.264 inches and 0.271 inches

Second Leg Distance Between Hole Centers Along Width:

4.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

3.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

9.000 inches

First Leg End Width:

8.500 inches

First Leg Distance Between Hole Centers Along Width:

5.000 inches

First Leg Distance From Edge To Hole Center Along Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Length:

0.688 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Product Name:

Bracket, mountin, spp

Special Features:

Second leg has 2 cutouts, 1.250 w x 0.125 h, centered in front of holes along open edge

Material:

Aluminum alloy 6061

Material Specification:

Astm b308, tamper t6 assn standard single material response

Surface Treatment:

Chromate and primer and paint

Surface Treatment Specification:

Mil-c-5541, class 1a military specification 1st treatment response and mil-p-24441/20 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.