## NSN 5340-01-509-8226

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-509-8226

Mounting Hole Type:
Plain
First Leg Length:
1.000 inches
Second Leg Length:
1.000 inches
End Application:
Asds residual
Second Leg Width:
1.250 inches
Second Leg Corner Radius:
0.380 inches
First Leg Hole Diameter:
Between 0.404 inches and 0.411 inches
Second Leg Hole Diameter:
Between 0.404 inches and 0.411 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.470 inches
First Leg Thickness:
0.125 inches
Second Leg Thickness:
0.125 inches
Center Section Height:
6.880 inches
Center Section Width:
1.250 inches
Center Section Thickness:
0.125 inches
First Leg Width:
1.250 inches
First Leg Corner Radius:
0.380 inches
First Leg Distance From Edge To Hole Center Along Width:
0.750 inches
First Leg Distance From Edge To Hole Center Along Length:
0.470 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
One hole

## NSN 5340-01-509-8226

Double Angle Bracket - Page 2 of 2



Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
One hole
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Product Name:
Bracket, mag switch, upper
Special Features:
$Bottom/center\ section\ is\ curved\ slightly-see\ drawing\ for\ details;\ center\ section\ has\ 2\ slots,\ 0.260\ w\ x\ 0.640\ I,\ centered\ 0.750\ from\ front$
edge and 1.570 & 5.810 from left edge
Material:
Nickel alloy
Material Specification:
Astam b443, inconel-625, condition annealed assn standard single material response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0