

View Online at <https://aerobasegroup.com/nsn/5340-01-509-8226>

Mounting Hole Type:

Plain

First Leg Length:

1.000 inches

Second Leg Length:

1.000 inches

End Application:

Asds residual

Second Leg Width:

1.250 inches

Second Leg Corner Radius:

0.380 inches

First Leg Hole Diameter:

Between 0.404 inches and 0.411 inches

Second Leg Hole Diameter:

Between 0.404 inches and 0.411 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.470 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

6.880 inches

Center Section Width:

1.250 inches

Center Section Thickness:

0.125 inches

First Leg Width:

1.250 inches

First Leg Corner Radius:

0.380 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.470 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Product Name:

Bracket, mag switch, upper

Special Features:

Bottom/center section is curved slightly-see drawing for details; center section has 2 slots, 0.260 w x 0.640 l, centered 0.750 from front edge and 1.570 & 5.810 from left edge

Material:

Nickel alloy

Material Specification:

Astam b443, inconel-625, condition annealed assn standard single material response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0