

View Online at <https://aerobasegroup.com/nsn/5340-01-509-8252>

Mounting Hole Type:

Plain

First Leg Length:

1.380 inches

Second Leg Length:

5.000 inches

Furnished Items (non-core):

Al bracket 1; 2ea al pad, 2.00 w x 2.875 l; 4ea screw, flat head, 100 ctsk (.250) no. 1/4-20 x .750 cres, passivate

Second Leg Width:

16.050 inches

First Leg Hole Diameter:

Between 0.219 inches and 0.225 inches

Second Leg Hole Diameter:

Between 0.404 inches and 0.411 inches

Second Leg Distance Between Hole Centers Along Width:

15.000 inches

Second Leg Distance Between Hole Centers Along Length:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.525 inches

Second Leg Distance From Edge To Hole Center Along Length:

3.750 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

16.050 inches

First Leg Corner Radius:

0.750 inches

First Leg Distance Between Hole Centers Along Width:

10.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

2.500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

5.000 inches

First Leg Distance From Edge To Hole Center Along Width:

2.086 inches

First Leg Distance From Edge To Hole Center Along Length:

0.300 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Cutout Length:

3.250 inches

Second Leg Cutout Width:

9.130 inches

Product Name:

Bracket, mounting, cold plate, pumps

Special Features:

Pads are fastened on top side of second leg with screws centered 2.520 and 13.645 from left edge and 1.750 and 3.750 from angle edge; second leg has 2 holes, 0.542-0.549 in diam. Centered between each line of screws; second leg's outer edges are rounded to radius of 0.750 and the inner corners to radius of 1.250

Material:

Aluminum alloy 6061

Material Specification:

Astm b308, temper t6 assn standard 1st material response and astm b209, temper t651 assn standard 2nd material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.