

View Online at <https://aerobasegroup.com/nsn/5340-01-509-8293>

Mounting Hole Type:

Plain

First Leg Length:

1.250 inches

Second Leg Length:

5.000 inches

Furnished Items (non-core):

Bracket 1; 2 ea. Pads, 2.0 x c 3.0 I; epoxy resin; curing agent; isopropyl alcohol

End Application:

Asds residual

Second Leg Width:

16.050 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

Between 0.404 inches and 0.411 inches

Second Leg Distance Between Hole Centers Along Width:

11.125 inches

Second Leg Distance Between Hole Centers Along Length:

2.875 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.525 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.875 inches

First Leg Thickness:

0.375 inches

Second Leg Thickness:

0.375 inches

First Leg Width:

16.050 inches

First Leg Corner Radius:

0.750 inches

First Leg Distance Between First And Second Hole Centers Along Width:

3.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

3.000 inches

First Leg Distance From Edge To Hole Center Along Width:

4.972 inches

First Leg Distance From Edge To Hole Center Along Length:

0.335 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Cut out

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Cutout Length:

3.250 inches

Second Leg Cutout Width:

9.130 inches

Product Name:

Bracket, mounting, cold plate, pumps

Special Features:

Pads are adhered to 2nd leg 0.92 from angle edge and 1.52 and 12.64 from left edge; 2nd leg's outer edges are rounded to radius of 0.750 and inner corners to radius of 1.12; 2 holes, 0.545-0.552 in diam, through both bracket and pad, are centered 2.425 from angle edge and 2.930 and 14.055 from left edge

Material:

Aluminum alloy 6061

Material Specification:

Astm b308, temper t6 assn standard 1st material response and astm b209, temper t651 federal specification 2nd material response

Surface Treatment:

Chromate and primer

Surface Treatment Specification:

Mil-c-5541, class 1a military specification 1st treatment response and mil-p-24441/20 military specification 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.