NSN 5340-01-509-8669

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-509-8669

View Online at https://aerobasegroup.com/nsn/5340-01-509-8669
Mounting Hole Type:
Plain
First Leg Length:
Between 2.790 inches and 3.350 inches
Second Leg Length:
3.350 inches
Furnished Items (non-core):
Rubber adhesive
Second Leg Width:
3.350 inches
First Leg Hole Diameter:
Between 0.529 inches and 0.536 inches
Second Leg Hole Diameter:
Between 0.404 inches and 0.411 inches
Second Leg Distance Between Hole Centers Along Length:
1.094 inches
Second Leg Distance From Edge To Hole Center Along Width:
1.000 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.671 inches
First Leg Thickness:
0.380 inches
Second Leg Thickness:
0.380 inches
First Leg Width:
2.000 inches
First Leg Distance From Edge To Hole Center Along Width:
1.000 inches
First Leg Distance From Edge To Hole Center Along Length:
1.213 inches
First Leg Style:
Square
First Leg Hole Arrangement Style:
One hole
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Two holes
Two holes Features Provided:
Two holes

Not identical

NSN 5340-01-509-8669

Angle Bracket - Page 2 of 2



First Leg Angle:
90.0 degrees
Special Features:
Second leg angles inward - see drawing for details
Material:
Titanium alloy and rubber neoprene
Material Specification:
Mil-t-9046, comp ab-2, 6al-4v, eli, condition annealed military specification 1st material response and astm d-2000-771 (2bc 415 a14 b14
c12 eo14 f17) assn standard 2nd material response
Surface Treatment:
Primer and paint
Surface Treatment Specification:
Mil-p-24441/29 military specification 1st treatment response and mil-p-24441/31 military specification 2nd treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-t-9046 spec.