# NSN 5340-01-509-8669

Angle Bracket - Page 1 of 2

Mounting Hole Type:

Plain

View Online at https://aerobasegroup.com/nsn/5340-01-509-8669



First Leg Length: Between 2.790 inches and 3.350 inches Second Leg Length: 3.350 inches Furnished Items (non-core): Rubber adhesive Second Leg Width: 3.350 inches First Leg Hole Diameter: Between 0.529 inches and 0.536 inches Second Leg Hole Diameter: Between 0.404 inches and 0.411 inches Second Leg Distance Between Hole Centers Along Length: 1.094 inches Second Leg Distance From Edge To Hole Center Along Width: 1.000 inches Second Leg Distance From Edge To Hole Center Along Length: 0.671 inches First Leg Thickness: 0.380 inches Second Leg Thickness: 0.380 inches First Leg Width: 2.000 inches First Leg Distance From Edge To Hole Center Along Width: 1.000 inches First Leg Distance From Edge To Hole Center Along Length: 1.213 inches First Leg Style: Square First Leg Hole Arrangement Style: One hole Second Leg Style: Square Second Leg Hole Arrangement Style: Two holes **Features Provided:** Cushion Second Leg Relationship To First Leg: Not identical

# NSN 5340-01-509-8669

Angle Bracket - Page 2 of 2



First Leg Angle:

90.0 degrees

#### **Special Features:**

Second leg angles inward - see drawing for details

### Material:

Titanium alloy and rubber neoprene

## Material Specification:

Mil-t-9046, comp ab-2, 6al-4v, eli, condition annealed military specification 1st material response and astm d-2000-771 (2bc 415 a14 b14

c12 eo14 f17) assn standard 2nd material response

## Surface Treatment:

Primer and paint

### **Surface Treatment Specification:**

Mil-p-24441/29 military specification 1st treatment response and mil-p-24441/31 military specification 2nd treatment response

# Style Designator:

Angle

## Shelf Life:

N/a

# Unit Of Measure:

---

### Demilitarization:

No

## Fiig:

A042a0

# Mil-std (military Standard):

Mil-t-9046 spec.