

View Online at <https://aerobasegroup.com/nsn/5340-01-509-8722>

**Mounting Hole Type:**

Plain

**First Leg Length:**

6.630 inches

**Second Leg Length:**

7.000 inches

**Second Leg Width:**

7.000 inches

**Second Leg Hole Diameter:**

Between 4.101 inches and 4.102 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

3.125 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

3.125 inches

**First Leg Thickness:**

0.750 inches

**Second Leg Thickness:**

1.830 inches

**First Leg Width:**

6.250 inches

**Second Leg Side Radius:**

3.130 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

No hole

**Second Leg Style:**

Side radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Bracket, interlock receiver

**Special Features:**

Top plate (first leg) is 7.0 x 7.0 with front left corner rounded to radius of 3.130 and with piece 3.88 w x 8.50 l x 0.75 thk attached at angle to right edge - see drawing for details; back plate (second leg) is 6.25 w x 6.63 h x 0.75 thk and is attached to back edge of top flush with left edge, leaving 0.75 in. Gap at right edge

**Material:**

Titanium alloy

**Material Specification:**

Mil-t-9046, comp a-b, condition annealed military specification single material response or -mil-t-9047, comp ti-6al- 4v, eli, condition

annealed military specification single material response

**Surface Treatment:**

Primer and paint

**Surface Treatment Specification:**

Mil-p-24441/29 military specification 1st treatment response and mil-p-24441/31 military specification 2nd treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-t-9046 spec.