

View Online at <https://aerobasegroup.com/nsn/5340-01-510-7674>

Cross Sectional Shape:

Flat, round rib reinforced

Hole Diameter:

Between 0.279 inches and 0.289 inches

Bolt Circle Diameter:

9.500 inches

Flange Thickness:

Between 0.285 inches and 0.345 inches

Outside Diameter:

Between 10.410 inches and 10.590 inches

Edge Shape:

Round, multi holes

Bolt Circle Hole Quantity:

8

Body Thickness:

0.690 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

Special Features:

Bottom edge is vented with grid of 1.56 inch square cutouts; bottom edge is rounded to radius of 0.13 inch

Material:

Aluminum alloy a356.0 and aluminum alloy 6061

Material Specification:

Astm b26, 356-t6, class 2b, grade d assn standard 1st material response and ams 4027, aa6061-t62, -t651 assn standard 2nd material response

Surface Treatment:

Primer epoxy-polyamide and paint polyurethane

Surface Treatment Specification:

Mil-p-24441/29, formula 150, type iv military specification 1st treatment response and fed-std-595, haze gray 26270 federal standard 2nd treatment response and mil-c-85285 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A531c0

Mil-std (military Standard):

Mil-p-24441 spec.