

View Online at <https://aerobasegroup.com/nsn/5340-01-511-0318>

**First Leg Length:**

2.250 inches

**Second Leg Length:**

1.380 inches

**End Application:**

Heavyweight torpedo, g&c tilt dolly

**Second Leg Width:**

2.250 inches

**Second Leg Hole Diameter:**

0.221 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.375 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.437 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.880 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

2.250 inches

**First Leg Style:**

Cut out

**First Leg Hole Arrangement Style:**

No hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

96.0 degrees

**First Leg Cutout Length:**

0.750 inches

**First Leg Cutout Width:**

0.437 inches

**Product Name:**

Swing bolt bracket

**Material:**

Steel comp 304l

**Material Specification:**

Astm-a666 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Astm-a967 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0