## NSN 5340-01-511-7402

Swivel Caster - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5340-01-511-7402

| view Offilite at https://aerobasegroup.com/hist//3040-01-311-7402   |
|---|
| Wheel Quantity:   |
| 1   |
| Safe Operating Load Rating:   |
| 900.0 pounds  |
| Material And Location:  |
| Steel, cast body err-100 err-100 or steel, forged body err-100 err-100 or aluminum alloy body err-100 err-100 |
| Surface Treatment And Location:   |
| Zinc plated plate err-100 err-100   |
| Wheel Type:   |
| Solid   |
| Wheel Diameter:   |
| 8.000 inches  |
| Effective Height:   |
| Between 9.380 inches and 9.620 inches   |
| Features Provided:  |
| Brake lock and swivel lock  |
| Plate Style:  |
| Square  |
| Wheel Bearing Type:   |
| Ball or annular ball  |
| Swivel Bearing Type:  |
| Ball or roller  |
| Tread Width:  |
| 2.000 inches  |
| Caster Plate Length:  |
| 4.500 inches  |
| Caster Plate Width:   |
| 4.000 inches  |
| Center To Center Major Distance Between Mounting Slots Along Length:  |
| 3.625 inches  |
| Center To Center Minor Distance Between Mounting Slots Along Length:  |
| 3.000 inches  |
| Center To Center Major Distance Between Mounting Slots Along Width:   |
| 3.000 inches  |
| Center To Center Minor Distance Between Mounting Slots Along Width:   |
| 2.625 inches  |
| Caster Plate Mounting Slot Width:   |
| 0.437 inches  |
| Style Designator:   |
| Swivel offset   |
| Shelf Life:   |

## NSN 5340-01-511-7402

Swivel Caster - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A25600