## NSN 5340-01-514-6963

Angle Bracket - Page 1 of 2





Mounting Hole Type:

Plain

First Leg Length:

4.000 inches

Second Leg Length:

2.250 inches

### Second Leg Width:

1.620 inches

#### First Leg Hole Diameter:

0.560 inches

## Second Leg Hole Diameter:

#### 0.560 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.810 inches

Second Leg Distance From Edge To Hole Center Along Length:

## 0.800 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

1.620 inches

## First Leg Distance Between Hole Centers Along Length:

1.880 inches

First Leg Distance From Edge To Hole Center Along Width:

0.810 inches

First Leg Distance From Edge To Hole Center Along Length:

0.335 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

#### Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

**First Leg Angle:** 

0.375 radians

**Product Name:** 

Angle, fitting

# NSN 5340-01-514-6963

Angle Bracket - Page 2 of 2



### **Special Features:**

Deburr holes and break sharp edges

## Material:

Aluminum

## Material Specification:

5052-h32 federal specification 1st material response

### Surface Treatment:

Aluminum alloy

## Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response and mil-p-53022 military specification 2nd treatment response

### Style Designator:

Angle

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A042a0

### Mil-std (military Standard):

Mil-c-5541 spec.