

View Online at <https://aerobasegroup.com/nsn/5340-01-514-7452>

Mounting Hole Type:

Plain

First Leg Length:

4.560 inches

Second Leg Length:

5.000 inches

Second Leg Width:

1.120 inches

First Leg Hole Diameter:

Between 0.221 inches and 0.234 inches

Second Leg Hole Diameter:

Between 0.265 inches and 0.281 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.218 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Thickness:

0.500 inches

Second Leg Thickness:

0.500 inches

First Leg Width:

2.310 inches

First Leg Distance Between Lower Hole Centers Along Width:

4.002 inches

First Leg Distance Between Hole Centers Along Length:

1.625 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.562 inches

First Leg Distance From Edge To Hole Center Along Width:

0.558 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Side radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.250 radians

Product Name:

Bracket, damper motor

Special Features:

Deburr holes and break sharp edges, primer, epoxy coating, corrosion inhibiting, lead and chromate free per mil-p-53022

Material:

Aluminum alloy 6061

Material Specification:

6061-t6 federal specification 1st material response

Surface Treatment:

Aluminum alloy

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.