

View Online at <https://aerobasegroup.com/nsn/5340-01-514-7452>

**Mounting Hole Type:**

Plain

**First Leg Length:**

4.560 inches

**Second Leg Length:**

5.000 inches

**Second Leg Width:**

1.120 inches

**First Leg Hole Diameter:**

Between 0.221 inches and 0.234 inches

**Second Leg Hole Diameter:**

Between 0.265 inches and 0.281 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.218 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Thickness:**

0.500 inches

**Second Leg Thickness:**

0.500 inches

**First Leg Width:**

2.310 inches

**First Leg Distance Between Lower Hole Centers Along Width:**

4.002 inches

**First Leg Distance Between Hole Centers Along Length:**

1.625 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.562 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.558 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Side radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.250 radians

**Product Name:**

Bracket, damper motor

**Special Features:**

Deburr holes and break sharp edges, primer, epoxy coating, corrosion inhibiting, lead and chromate free per mil-p-53022

**Material:**

Aluminum alloy 6061

**Material Specification:**

6061-t6 federal specification 1st material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.