

View Online at <https://aerobasegroup.com/nsn/5340-01-514-7821>

Mounting Hole Type:

Counterbored and threaded

First Leg Length:

1.562 inches

Second Leg Length:

2.000 inches

End Application:

0000llcqa6519; w/s: seal delivery vehicle

Second Leg Width:

4.000 inches

First Leg Hole Diameter:

Between 0.014 inches and 0.028 inches

Second Leg Hole Diameter:

Between 0.404 inches and 0.410 inches

Second Leg Distance Between Hole Centers Along Width:

3.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.687 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.000 inches

First Leg Distance Between Hole Centers Along Width:

2.500 inches

First Leg Distance Between Hole Centers Along Length:

1.412 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.293 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 6061

Material Specification:

-astm-b308, temper t6 assn standard single material response

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.