

View Online at <https://aerobasegroup.com/nsn/5340-01-514-7821>

**Mounting Hole Type:**

Counterbored and threaded

**First Leg Length:**

1.562 inches

**Second Leg Length:**

2.000 inches

**End Application:**

0000llcqa6519; w/s: seal delivery vehicle

**Second Leg Width:**

4.000 inches

**First Leg Hole Diameter:**

Between 0.014 inches and 0.028 inches

**Second Leg Hole Diameter:**

Between 0.404 inches and 0.410 inches

**Second Leg Distance Between Hole Centers Along Width:**

3.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.687 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

4.000 inches

**First Leg Distance Between Hole Centers Along Width:**

2.500 inches

**First Leg Distance Between Hole Centers Along Length:**

1.412 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.293 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Four holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

-astm-b308, temper t6 assn standard single material response

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-c-5541, class 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.