

View Online at <https://aerobasegroup.com/nsn/5340-01-515-4173>

First Leg Length:

1.720 inches

Second Leg Length:

1.720 inches

Second Leg Width:

4.000 inches

First Leg Hole Diameter:

0.688 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

Center Section Height:

3.630 inches

Center Section Width:

4.000 inches

Center Section Thickness:

0.190 inches

First Leg Width:

4.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.120 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.120 inches

First Leg Distance From Edge To Hole Center Along Width:

0.880 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Side radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.380 radians

Second Leg Angle:

0.380 radians

Product Name:

Bracket, lower, ground rod

Special Features:

Range of motion 90 degree lh or rh stopped and detained

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification 1st material response

Surface Treatment:

Primer

Surface Treatment Specification:

Mil-o-53022 military specification 1st treatment response and mil-c-22750 military specification 2nd treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-o-53022 spec.