

View Online at <https://aerobasegroup.com/nsn/5340-01-516-3318>

Mounting Hole Type:

Plain

First Leg Length:

Between 0.980 inches and 1.020 inches

Second Leg Length:

Between 1.670 inches and 1.710 inches

Second Leg Width:

Between 7.980 inches and 8.020 inches

Second Leg End Width:

Between 7.740 inches and 7.780 inches

First Leg Hole Diameter:

0.185 inches

Second Leg Hole Diameter:

0.281 inches

Second Leg Distance Between Hole Centers Along Width:

4.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.436 inches

First Leg Thickness:

Between 0.120 inches and 0.130 inches

Second Leg Thickness:

Between 0.120 inches and 0.130 inches

First Leg Width:

Between 7.980 inches and 8.020 inches

First Leg End Width:

Between 7.740 inches and 7.780 inches

First Leg Distance Between Hole Centers Along Width:

4.750 inches

First Leg Distance From Edge To Hole Center Along Width:

1.625 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Product Name:

Bracket, mounting

Material:

Aluminum alloy 6063

Material Specification:

Temper t52 assn standard single material response

Surface Treatment:

Primer and paint

Surface Treatment Specification:

Mil-p-24441/20 military specification 1st treatment response and 639435-15 mfr ref 2nd treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-p-24441 spec.