NSN 5340-01-516-9746

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-516-9746 **Thread Class:** 2b flange hole **Thread Direction:** Right-hand flange hole Thread Length: 1.630 inches left internal (includes through thread) Flange Thickness: Between 0.250 inches and 0.350 inches Length: Between 1.380 inches and 1.390 inches **Corner Radius:** 0.020 inches **Cross-sectional Length:** 1.630 inches **Cross-sectional Width:** 2.000 inches Flange Width Across Flats: 1.800 inches **End Application:** Tow point release **Cross-sectional Shape:** Elliptical Width Across Flats: 1.800 inches Thready Qty Per Inch (tpi): 20 flange hole **Thread Size:** 0.250 inches flange hole **Special Features:** Standoff pin, lever tow point Material: Titanium alloy uns r56400 **Material Specification:** Mil-t-9047, t1-6al-4v (eli), condition a military specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Ams 2488c assn standard single treatment response or mis 23545, type 2 military specification single treatment response **Style Designator:** Flanged left internal thread **Thread Series Designator:**

Unc flange hole

NSN 5340-01-516-9746

Spacing Threaded Standoff - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A08900	

Mil-std (military Standard):

Mil-t-9047 spec.

Shelf Life: