NSN 5340-01-517-0664

Flare Lock Fastener - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-517-0664

Thread	Class:

3b

Thread Direction:

Right-hand

Thread Length:

0.333 inches

Head Style:

Dished countersunk

Head Diameter:

0.431 inches

Head Height:

0.104 inches

Internal Drive Style:

Cross recess

Hole Size For Which Designed:

0.264 inches

Material Thickness Range For Which Designed:

+0.432/+0.442 inches

Screw Minimum Length For Which Designed:

0.432 inches

Thready Qty Per Inch (tpi):

12-48

Thread Size:

0.265 inches

Product Name:

Sleeve-adjustable preload, self sustaining, positive mechanical lock, 100 degree flush head, long thread, inconel 718 (108 ksi fsu).

Err Default:

Err default

Material:

Nickel alloy

Material Specification:

Inco 718 (108 ksi fsu) federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Countersunk sleeve

Thread Series Designator:

Uns

Shelf Life:

N/a

NSN 5340-01-517-0664

Flare Lock Fastener - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A03100

