

View Online at <https://aerobasegroup.com/nsn/5340-01-518-8831>

Mounting Hole Type:

Countersunk

First Leg Length:

2.000 inches

Second Leg Length:

2.630 inches

End Application:

Angle, mounting

Second Leg Width:

2.000 inches

First Leg Hole Diameter:

Between 0.338 inches and 0.343 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

6.375 inches

Second Leg Distance Between Second And Third Hole Centers Along Width:

6.375 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.958 inches

Second Leg Slot Length:

1.100 inches

Second Leg Slot Width:

Between 0.255 inches and 0.275 inches

Second Leg Distance Between Third And Fourth Hole Centers Along Width:

6.375 inches

First Leg Thickness:

0.188 inches

Second Leg Thickness:

0.188 inches

First Leg Width:

2.000 inches

First Leg Distance Between Hole Centers Along Width:

14.000 inches

First Leg Distance Between First And Second Hole Centers Along Width:

4.000 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

6.250 inches

First Leg Distance From Edge To Hole Center Along Width:

3.750 inches

First Leg Distance From Edge To Hole Center Along Length:

0.940 inches

First Leg Side Radius:

0.190 inches

Second Leg Side Radius:

0.190 inches

First Leg Style:

Side radius

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Side radius

Second Leg Hole Arrangement Style:

4 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Angle

Material:

Aluminum alloy 6063

Material Specification:

Astm b221, 6063, temper t52 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type iii, class 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.