

View Online at <https://aerobasegroup.com/nsn/5340-01-518-9537>

**Mounting Hole Type:**

Countersunk and plain

**First Leg Length:**

Between 0.840 inches and 0.900 inches

**Second Leg Length:**

Between 0.970 inches and 1.030 inches

**End Application:**

Installation and equipment kit, shelter

**Second Leg Width:**

Between 3.470 inches and 3.530 inches

**Second Leg End Width:**

Between 3.170 inches and 3.350 inches

**First Leg Slot Length:**

Between 0.370 inches and 0.380 inches

**First Leg Slot Width:**

Between 0.245 inches and 0.255 inches

**Second Leg Hole Diameter:**

Between 0.151 inches and 0.161 inches

**First Leg Thickness:**

Between 0.085 inches and 0.095 inches

**Second Leg Thickness:**

Between 0.085 inches and 0.095 inches

**First Leg Width:**

Between 3.470 inches and 3.530 inches

**First Leg End Width:**

Between 3.170 inches and 3.350 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 2.245 inches and 2.255 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.590 inches and 0.650 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.310 inches and 0.370 inches

**First Leg Style:**

Chamfered ends

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Chamfered ends

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Chamfer Angle:**

45.0 degrees

**Second Leg Chamfer Angle:**

45.0 degrees

**Special Features:**

Second leg has 8 countersunk holes; bracket angle radius 0.060/0.120

**Material:**

Aluminum alloy 5052

**Material Specification:**

Astm b209 sheet 502 tempter h32 federal specification single material response

**Surface Treatment Specification:**

Qq-c-22750 federal specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0