Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-519-0138

# Thread Class:

2b right external

Thread Direction:

Right-hand right external

## Thread Length:

0.438 inches left internal (includes through thread)

## Length:

Between 0.995 inches and 1.005 inches

## **Cross-sectional Length:**

Between 1.266 inches and 1.384 inches

## Cross-sectional Width:

Between 0.244 inches and 0.256 inches

## **End Application:**

Post, electrical-mechanical equipment, stud type

## **Cross-sectional Shape:**

Hexagon

## Width Across Flats:

0.250 inches

## Thready Qty Per Inch (tpi):

32 right external

## Thread Size:

0.438 inches left internal (includes through thread)

## **Right Projection Diameter:**

0.164 inches

## **Right Projection Length:**

Between 0.371 inches and 0.379 inches

## Material:

Aluminum alloy 6061 or aluminum alloy 2024 or aluminum alloy 2011

## Material Specification:

Qq-a-225/8, temper t6 federal specification 1st material response or qq-a-225/6, temper t4 federal specification 2nd material response or

qq-a-225/3, temper t4 federal specification 3rd material response

## Surface Treatment:

Anodize

## Surface Treatment Specification:

Mil-a-8625, type i or ii, class 1 military specification single treatment response

## Style Designator:

Left internal and right external thread

## **Thread Series Designator:**

Unc right external

## Shelf Life:

N/a

## Unit Of Measure:

## NSN 5340-01-519-0138

Spacing Threaded Standoff - Page 2 of 2



Demilitarization:

No

Fiig:

A08900

Mil-std (military Standard):

Mil-a-8625 spec.