

View Online at <https://aerobasegroup.com/nsn/5340-01-519-0167>

Mounting Hole Type:

Plain

First Leg Length:

1.500 inches

Second Leg Length:

2.000 inches

Second Leg Width:

1.000 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

Between 0.389 inches and 0.396 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

5.000 inches

Center Section Width:

1.000 inches

Center Section Thickness:

1.250 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Product Name:

Holder, valve handle

Special Features:

Bcenter section of bracket has 3 additional mounting holes (two having diameter of 0.125 inches and one having diameter of 0.190 inches);
bracket has chemical conversion coating surface treatment

Material:

Aluminum alloy 5052

Material Specification:

Astm-b209, t h32 assn standard single material response

Surface Treatment Specification:

Mil-c-5542, cl 1a military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5542 spec.