

View Online at <https://aerobasegroup.com/nsn/5340-01-519-0167>

**Mounting Hole Type:**

Plain

**First Leg Length:**

1.500 inches

**Second Leg Length:**

2.000 inches

**Second Leg Width:**

1.000 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.389 inches and 0.396 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**Center Section Height:**

5.000 inches

**Center Section Width:**

1.000 inches

**Center Section Thickness:**

1.250 inches

**First Leg Width:**

1.000 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

No hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Product Name:**

Holder, valve handle

**Special Features:**

Bcenter section of bracket has 3 additional mounting holes (two having diameter of 0.125 inches and one having diameter of 0.190 inches);  
bracket has chemical conversion coating surface treatment

**Material:**

Aluminum alloy 5052

**Material Specification:**

Astm-b209, t h32 assn standard single material response

**Surface Treatment Specification:**

Mil-c-5542, cl 1a military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5542 spec.