

View Online at <https://aerobasegroup.com/nsn/5340-01-519-0931>

**Mounting Hole Type:**

Plain

**First Leg Length:**

3.000 inches

**Second Leg Length:**

4.000 inches

**End Application:**

Bracket, sensor

**Second Leg Width:**

4.000 inches

**First Leg Hole Diameter:**

Between 0.278 inches and 0.289 inches

**Second Leg Hole Diameter:**

Between 0.203 inches and 0.208 inches

**Second Leg Distance Between Hole Centers Along Width:**

3.197 inches

**Second Leg Distance Between Hole Centers Along Length:**

3.197 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.600 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

4.000 inches

**First Leg Distance Between Hole Centers Along Width:**

2.000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.500 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Bracket has (1) center hole (1.4"-1.6" dia); second leg hole arrangement different from first leg, refer to drawing for specifications.

**Material:**

Aluminum alloy 6061

**Material Specification:**

Astm b308, temper t6 assn standard single material response

**Surface Treatment Specification:**

Mil-I-5541, class 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-I-5541 spec.