

View Online at <https://aerobasegroup.com/nsn/5340-01-519-0931>

Mounting Hole Type:

Plain

First Leg Length:

3.000 inches

Second Leg Length:

4.000 inches

End Application:

Bracket, sensor

Second Leg Width:

4.000 inches

First Leg Hole Diameter:

Between 0.278 inches and 0.289 inches

Second Leg Hole Diameter:

Between 0.203 inches and 0.208 inches

Second Leg Distance Between Hole Centers Along Width:

3.197 inches

Second Leg Distance Between Hole Centers Along Length:

3.197 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.600 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.000 inches

First Leg Distance Between Hole Centers Along Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.500 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Special Features:

Bracket has (1) center hole (1.4"-1.6" dia); second leg hole arrangement different from first leg, refer to drawing for specifications.

Material:

Aluminum alloy 6061

Material Specification:

Astm b308, temper t6 assn standard single material response

Surface Treatment Specification:

Mil-I-5541, class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-I-5541 spec.