

View Online at <https://aerobasegroup.com/nsn/5340-01-519-4265>

Mounting Hole Type:

Plain

First Leg Length:

0.500 inches

Second Leg Length:

0.500 inches

End Application:

Bracket, signal lamp

Second Leg Width:

1.300 inches

Second Leg End Width:

0.680 inches

First Leg Hole Diameter:

0.144 inches

Second Leg Hole Diameter:

0.257 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.600 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Thickness:

0.060 inches

Second Leg Thickness:

0.060 inches

First Leg Width:

1.300 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.150 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Material:

Aluminum alloy 6063

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 2, black military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.