

View Online at <https://aerobasegroup.com/nsn/5340-01-520-9068>

**Mounting Hole Type:**

Plain

**First Leg Length:**

2.340 inches

**Second Leg Length:**

10.120 inches

**End Application:**

Operating gear

**Second Leg Width:**

0.620 inches

**First Leg Hole Diameter:**

0.250 inches

**Second Leg Hole Diameter:**

0.250 inches

**Second Leg Distance Between Hole Centers Along Length:**

6.310 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.400 inches

**Second Leg Distance Between First And Second Hole Centers Along Length:**

2.110 inches

**Second Leg Distance Between Second And Third Hole Centers Along Length:**

2.100 inches

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

0.620 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.030 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Has fifth hole on second leg positioned 2.100 inches from 4th hole; for use on generator exhaust louver installation

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 military specification single material response

**Surface Treatment:**

Anodize and primer epoxy and plastic epoxy

**Surface Treatment Specification:**

Mil-a-8625ty2cl1 military specification 1st treatment response and mil-p-23377 military specification 2nd treatment response and mil-c-22750 military specification 3rd treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

spec.