

View Online at <https://aerobasegroup.com/nsn/5340-01-520-9085>

Mounting Hole Type:

Plain

First Leg Length:

5.720 inches

Second Leg Length:

1.940 inches

End Application:

Opening gear

Second Leg Width:

0.620 inches

First Leg Hole Diameter:

0.250 inches

Second Leg Hole Diameter:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.400 inches

Second Leg Distance Between First And Second Hole Centers Along Length:

2.240 inches

Second Leg Distance Between Second And Third Hole Centers Along Length:

2.240 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

3.850 inches

Center Section Width:

0.620 inches

Center Section Thickness:

0.125 inches

First Leg Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.690 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

175.0 degrees

Second Leg Angle:

110.0 degrees

Special Features:

Barea between legs has two mounting holes spaced 2.000 inches apart beginning at a position 1.290 inches from 110 degree angle (off of first leg); for use on generator exhaust louver installation

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 military specification single material response

Surface Treatment:

Anodize and primer epoxy and plastic epoxy

Surface Treatment Specification:

Damil-a-8625ty2cl1 military specification 1st treatment response and mil-p-23377 military specification 2nd treatment response and mil-c-22750 military specification 3rd treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

spec.