

View Online at <https://aerobasegroup.com/nsn/5340-01-523-1118>

Mounting Hole Type:

Plain

First Leg Length:

1.750 inches

Second Leg Length:

4.500 inches

End Application:

Aps137 hpd

Second Leg Width:

0.750 inches

Second Leg Corner Radius:

0.130 inches

First Leg Slot Length:

0.625 inches

First Leg Slot Width:

0.270 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.375 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.716 inches

Second Leg Slot Length:

1.188 inches

Second Leg Slot Width:

0.210 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

0.750 inches

First Leg Corner Radius:

0.130 inches

First Leg Distance Between Hole Centers Along Length:

3.375 inches

First Leg Distance From Edge To Hole Center Along Width:

0.240 inches

First Leg Distance From Edge To Hole Center Along Length:

0.592 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Slot Offset Angle:

0.001 degrees

Product Name:

Piu bracket

Special Features:

Surface treatment is a chemical conversion coating

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment Specification:

Mil-c-5541, cl3 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.