

View Online at <https://aerobasegroup.com/nsn/5340-01-524-1803>

First Leg Length:

3.375 inches

Second Leg Length:

3.905 inches

End Application:

ENDI-TE-MNS-N:23

Second Leg Width:

3.680 inches

Second Leg End Width:

3.300 inches

First Leg Hole Diameter:

Between 0.405 inches and 0.420 inches

Second Leg Hole Diameter:

Between 0.250 inches and 0.280 inches

Second Leg Distance Between Hole Centers Along Width:

2.937 inches

Second Leg Distance Between Hole Centers Along Length:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.373 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.313 inches

First Leg Thickness:

Between 0.375 inches and 0.385 inches

Second Leg Thickness:

Between 0.375 inches and 0.385 inches

First Leg Width:

4.000 inches

First Leg End Width:

3.620 inches

First Leg Distance Between Hole Centers Along Width:

3.000 inches

First Leg Distance Between Hole Centers Along Length:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

Four holes

Second Leg Style:

Chamfered ends

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Second Leg Chamfer Angle:

45.0 degrees

Product Name:

Bracket, angle

Special Features:

For optional material application and thickness, see dwg.

Material:

Aluminum alloy 5083 or aluminum alloy 5086

Material Specification:

H321. Astm b209 assn standard 1st material response or h112. Astm b221 assn standard 1st material response or h32 or h116. Astm b209 assn standard 2nd material response or h112. Astm b221 assn standard 2nd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0