

View Online at <https://aerobasegroup.com/nsn/5340-01-524-3390>

**First Leg Length:**

7.250 inches

**Second Leg Length:**

2.750 inches

**End Application:**

ENDI-TE-MNS-N:23

**Second Leg Width:**

1.500 inches

**First Leg Slot Length:**

0.405 inches

**First Leg Slot Width:**

1.030 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.940 inches

**Second Leg Slot Length:**

0.405 inches

**Second Leg Slot Width:**

1.030 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.000 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

For optional material application and specifications, see dwg.

**Material:**

Aluminum alloy 5083 or aluminum alloy 5086

**Material Specification:**

H321.Astm b209 assn standard 1st material response or h111 or h112.Astm b221 assn standard 1st material response or h32 or h116.Astm b209 assn standard 2nd material response or h111 or h112.Astm b221 assn standard 2nd material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Per dwg 19207-12369001 mfr ref all treatment responses

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0