

View Online at <https://aerobasegroup.com/nsn/5340-01-526-2898>

**First Leg Length:**

2.750 inches

**Second Leg Length:**

2.380 inches

**End Application:**

ENDI-TE-MNS-N:23

**Second Leg Width:**

1.380 inches

**Second Leg Corner Radius:**

0.120 inches

**First Leg Hole Diameter:**

0.433 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.690 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.880 inches

**Second Leg Slot Length:**

1.180 inches

**Second Leg Slot Width:**

0.433 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

1.380 inches

**First Leg Corner Radius:**

0.120 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.690 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.620 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Slot Offset Angle:**

Between 25.0 degrees and 35.0 degrees

**Product Name:**

Bracket, hose, o l

**Special Features:**

Material shall have 24000 psi min ys and 40000 psi min ts, per dwg.

**Material:**

Aluminum alloy 5083 or aluminum alloy 5056

**Material Specification:**

H321 specification astm b209 assn standard 1st material response or h32 or h116.H32 or h116 astm b209 assn standard 2nd material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0