

View Online at <https://aerobasegroup.com/nsn/5340-01-526-2898>

First Leg Length:

2.750 inches

Second Leg Length:

2.380 inches

End Application:

ENDI-TE-MNS-N:23

Second Leg Width:

1.380 inches

Second Leg Corner Radius:

0.120 inches

First Leg Hole Diameter:

0.433 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.690 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.880 inches

Second Leg Slot Length:

1.180 inches

Second Leg Slot Width:

0.433 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

1.380 inches

First Leg Corner Radius:

0.120 inches

First Leg Distance From Edge To Hole Center Along Width:

0.690 inches

First Leg Distance From Edge To Hole Center Along Length:

0.620 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Slot Offset Angle:

Between 25.0 degrees and 35.0 degrees

Product Name:

Bracket, hose, o l

Special Features:

Material shall have 24000 psi min ys and 40000 psi min ts, per dwg.

Material:

Aluminum alloy 5083 or aluminum alloy 5056

Material Specification:

H321 specification astm b209 assn standard 1st material response or h32 or h116.H32 or h116 astm b209 assn standard 2nd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0