

View Online at <https://aerobasegroup.com/nsn/5340-01-526-6186>

**End Application:**

Generator, electrical power

**First Leg Slot Width:**

0.800 inches

**First Leg Thickness:**

0.390 inches

**Second Leg Thickness:**

0.390 inches

**Center Section Height:**

5.500 inches

**Center Section Width:**

17.000 inches

**Center Section Thickness:**

0.390 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.600 inches

**First Leg Distance Between First And Second Hole Centers Along Length:**

5.050 inches

**First Leg Hole Arrangement Style:**

3 slots

**Second Leg Hole Arrangement Style:**

3 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Lifting bracket, right

**Special Features:**

First leg is rectangular with 2 notches and 3 slots; center section has 90 degree corners at one end, and angles at opposite end; second leg is triangular in shape, with one off-center hole.

**Material:**

Steel

**Material Specification:**

Astm a36 assn standard single material response

**Surface Treatment:**

Primer

**Surface Treatment Specification:**

Mil-p-53030 military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-p-53030 spec.