

View Online at <https://aerobasegroup.com/nsn/5340-01-528-7504>

**Overall Length:**

Between 2.448 inches and 2.468 inches

**Overall Width:**

Between 0.625 inches and 0.640 inches

**Distance Between Mounting Hole Centers:**

Between 2.198 inches and 2.218 inches

**Cushioning Material:**

Plastic, tetrafluoroethylene

**Cushion:**

Included

**Mounting Pad:**

Not included

**Mounting Hole Size:**

Between 0.213 inches and 0.223 inches

**Distance Between Base And Inside Of Arch:**

Between 1.370 inches and 1.410 inches

**Product Name:**

Clamp assembly, saddle-type, cushioned, ptfe, 321 cres, -320 degrees f to 450 degrees f, general purpose.

**Special Features:**

Tensile strength of 100-120 ksi required on 321 cres sheet material. Cushion - strap and saddle polytetrafluoroethylene sheet strip per astm-d-1457 type i, extrude and heat formed to shape; color - white

**Material:**

Steel, ams 5510

**Material:**

Steel comp 321

**Surface Treatment:**

Passivate

**Style Designator:**

Saddle arch

**Surface Treatment:**

Passivated

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T372-a