## NSN 5340-01-530-6031

**Thread Class:** 

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-530-6031

| 2b right internal   |
|---|
| Thread Direction:   |
| Right-hand right internal                                 |
| Diameter:   |
| 0.250 inches  |
| Length:   |
| 1.986 inches  |
| Cross-sectional Shape:                                    |
| Round   |
| Right End Chamfer Depth:                                  |
| 0.005 inches  |
| Left End Chamfer Depth:                                   |
| 0.005 inches  |
| Thready Qty Per Inch (tpi):                               |
| 40 right internal   |
| Thread Size:  |
| 0.190 inches right internal                               |
| Left Projection Diameter:                                 |
| 0.187 inches  |
| Left Projection Length:                                   |
| Between 0.043 inches and 0.048 inches                     |
| Right Projection Diameter:                                |
| 0.187 inches  |
| Right Projection Length:                                  |
| Between 0.043 inches and 0.048 inches                     |
| Left End Chamfer Angle:                                   |
| Between 40.0 degrees and 50.0 degrees                     |
| Right End Chamfer Angle:                                  |
| Between 40.0 degrees and 50.0 degrees                     |
| Material:   |
| Aluminum alloy 6061                                       |
| Material Specification:                                   |
| Qq-a-200/8 federal specification single material response |
| Style Designator:   |
| Projection both ends left and right internal threads      |
| Thread Series Designator:                                 |
| Unc right internal  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5340-01-530-6031

Spacing Threaded Standoff - Page 2 of 2



Demilitarization:

No

Fiig:

A08900