

View Online at <https://aerobasegroup.com/nsn/5340-01-531-2620>

First Leg Length:

0.800 inches

Second Leg Length:

1.250 inches

End Application:

An/gsc-52 (v)1 and (v) 2

Second Leg Width:

3.200 inches

First Leg Hole Diameter:

Between 0.264 inches and 0.268 inches

Second Leg Distance Between Hole Centers Along Width:

2.320 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.440 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.520 inches

Second Leg Slot Length:

0.800 inches

Second Leg Slot Width:

0.204 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

3.200 inches

First Leg Distance Between Hole Centers Along Width:

2.320 inches

First Leg Distance From Edge To Hole Center Along Width:

0.440 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

2 slots

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Product Name:

Bracket assembly, waveguide

Special Features:

Finish - chem film iaw mil-c-5541, cl 1a

Material:

Aluminum alloy 5052

Material Specification:

Astm b209, 5052-h32 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0