

View Online at <https://aerobasegroup.com/nsn/5340-01-531-2620>

**First Leg Length:**

0.800 inches

**Second Leg Length:**

1.250 inches

**End Application:**

An/gsc-52 (v)1 and (v) 2

**Second Leg Width:**

3.200 inches

**First Leg Hole Diameter:**

Between 0.264 inches and 0.268 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.320 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.440 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.520 inches

**Second Leg Slot Length:**

0.800 inches

**Second Leg Slot Width:**

0.204 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

3.200 inches

**First Leg Distance Between Hole Centers Along Width:**

2.320 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.440 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.310 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

2 slots

**Features Provided:**

Nut

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Product Name:**

Bracket assembly, waveguide

**Special Features:**

Finish - chem film iaw mil-c-5541, cl 1a

**Material:**

Aluminum alloy 5052

**Material Specification:**

Astm b209, 5052-h32 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0