

View Online at <https://aerobasegroup.com/nsn/5340-01-534-5158>

First Leg Length:

1.120 inches

Second Leg Length:

2.750 inches

Second Leg Width:

2.750 inches

Second Leg Corner Radius:

0.500 inches

First Leg Slot Length:

0.380 inches

First Leg Slot Width:

0.218 inches

Second Leg Hole Diameter:

Between 0.382 inches and 0.391 inches

Second Leg Distance Between Hole Centers Along Width:

4.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.000 inches

Second Leg Distance From Edge To Hole Center Along Length:

1.750 inches

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

1.120 inches

First Leg Corner Radius:

0.500 inches

First Leg Distance Between Hole Centers Along Width:

3.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.350 inches

First Leg Distance From Edge To Hole Center Along Length:

0.750 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.