

View Online at <https://aerobasegroup.com/nsn/5340-01-534-5159>

**First Leg Length:**

0.750 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

3.500 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.198 inches and 0.204 inches

**Second Leg Hole Diameter:**

Between 0.268 inches and 0.271 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.000 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.440 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

3.500 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

2.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.440 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.