

View Online at <https://aerobasegroup.com/nsn/5340-01-534-6065>

First Leg Length:

0.830 inches

Second Leg Length:

3.000 inches

Second Leg Width:

2.750 inches

Second Leg Corner Radius:

0.250 inches

First Leg Hole Diameter:

Between 0.210 inches and 0.216 inches

Second Leg Hole Diameter:

Between 0.193 inches and 0.199 inches

Second Leg Distance Between Hole Centers Along Width:

1.750 inches

Second Leg Distance Between Hole Centers Along Length:

1.450 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.700 inches

First Leg Thickness:

1.250 inches

Second Leg Thickness:

1.250 inches

First Leg Width:

2.750 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.