

View Online at <https://aerobasegroup.com/nsn/5340-01-534-6065>

**First Leg Length:**

0.830 inches

**Second Leg Length:**

3.000 inches

**Second Leg Width:**

2.750 inches

**Second Leg Corner Radius:**

0.250 inches

**First Leg Hole Diameter:**

Between 0.210 inches and 0.216 inches

**Second Leg Hole Diameter:**

Between 0.193 inches and 0.199 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.750 inches

**Second Leg Distance Between Hole Centers Along Length:**

1.450 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.700 inches

**First Leg Thickness:**

1.250 inches

**Second Leg Thickness:**

1.250 inches

**First Leg Width:**

2.750 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.