

View Online at <https://aerobasegroup.com/nsn/5340-01-538-3178>

First Leg Length:

1.510 inches

Second Leg Length:

1.640 inches

Second Leg Width:

Between 0.590 inches and 0.650 inches

First Leg Hole Diameter:

0.098 inches

Second Leg Hole Diameter:

0.098 inches

Second Leg Distance Between Hole Centers Along Length:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

Between 0.590 inches and 0.650 inches

First Leg Distance Between Hole Centers Along Length:

0.620 inches

First Leg Distance From Edge To Hole Center Along Width:

0.310 inches

First Leg Distance From Edge To Hole Center Along Length:

0.310 inches

First Leg End Radius:

Between 0.400 inches and 0.460 inches

Second Leg End Radius:

Between 0.400 inches and 0.460 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Offset Angle:

12.0 degrees

Product Name:

Bracket angle formed, unequal legs .040 gage

Material:

Aluminum alloy 7075

Material Specification:

Qq-a-250/13, t6 military specification single material response

Surface Treatment:

Anodize and primer

Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 1st treatment response and mil-p-8585 military specification 2nd treatment response

Style Designator:

Offset angle

Specification Data:

78286 - ss1082 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

spec.