## NSN 5340-01-540-9935

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-540-9935

First Leg Length:
3.400 inches
Second Leg Length:
2.900 inches
End Application:
Nsn 1240-01-425-5464; intregrated sight as; w/s: missile, tow (ground i & ii)
First Leg Hole Diameter:
0.139 mils and 0.146 centimeters
Second Leg Hole Diameter:
0.120 inches
Second Leg Distance Between Hole Centers Along Length:
2.900 inches
Second Leg Distance From Edge To Hole Center Along Length:
2.400 inches
Center Section Height:
0.400 inches
Center Section Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Width:
0.250 inches
First Leg Distance From Edge To Hole Center Along Length:
0.200 inches
First Leg Style:
End radius
First Leg Hole Arrangement Style:
One hole
Second Leg Style:
Square
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Product Name:
Bracket, harness
Material:
Aluminum alloy 6061 and aluminum alloy 5052

**Material Specification:** 

Qq-a-250/11 federal specification 1st material response and qq-a-250/8, h32 or h34 federal specification 2nd material response

## NSN 5340-01-540-9935

Double Angle Bracket - Page 2 of 2

Mil-a-8625 spec.



Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type ii, class 2, color: black military specification single treatment response
Style Designator:
Adjacent angles
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):