## NSN 5340-01-542-5463

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-542-5463 **Thread Class:** 2b left internal (includes through thread) **Thread Direction:** Right-hand right external Thread Length: 0.250 inches right external Length: 0.625 inches **Cross-sectional Shape:** Hexagon Width Across Flats: 0.250 inches Thready Qty Per Inch (tpi): 40 left internal (includes through thread) **Thread Size:** 0.112 inches left internal (includes through thread) **Product Name:** Post, electrical-mechanical equipment, stud type **Right Projection Diameter:** 0.138 inches **Right Projection Length:** 0.250 inches Material: Aluminum alloy 6061 or aluminum alloy 2024 or aluminum alloy 2011 **Material Specification:** Qq-a-225/8 federal specification single material response or qq-a-225/6 federal specification single material response or qq-a-225/3 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response or mil-a-8625, type 2 military specification single treatment response **Style Designator:** Left internal and right external thread **Thread Series Designator:** Unf left internal (includes through thread) Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A08900

No

## NSN 5340-01-542-5463

Spacing Threaded Standoff - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.