

View Online at <https://aerobasegroup.com/nsn/5340-01-547-6164>

Mounting Hole Diameter:

0.125 inches

Center To Center Distance Between Mounting Holes Along Width:

Between 1.062 inches and 1.067 inches

Center To Center Distance Between Mounting Holes Along Length:

Between 1.062 inches and 1.067 inches

End Application:

F-22 raptor

Product Name:

Catch, clamping

Lever Offset Distance:

0.100 inches

Bolt Offset Distance:

0.240 inches

Special Features:

Buttons-material 2024-t3, 2024-t351, 2024-t4 per qq-a-250/4 or qq-a-225/6, finish anodize per mil-a-8625 typeii, gasket-material synthetic rubber per ams 3240 (40 shore)

Material:

Steel comp 631 spring

Material Specification:

Mil-s-5059 military specification 1st material response mounting bracket or mil-s-25043 military specification 1st material response mounting bracket or ams5673 assn standard 2nd material response mounting bracket

Surface Treatment:

Passivate spring

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spring

Style Designator:

Button actuator

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A10600

Mil-std (military Standard):

Mil-s-5059 spec.