

View Online at <https://aerobasegroup.com/nsn/5340-01-547-6164>

**Mounting Hole Diameter:**

0.125 inches

**Center To Center Distance Between Mounting Holes Along Width:**

Between 1.062 inches and 1.067 inches

**Center To Center Distance Between Mounting Holes Along Length:**

Between 1.062 inches and 1.067 inches

**End Application:**

F-22 raptor

**Product Name:**

Catch, clamping

**Lever Offset Distance:**

0.100 inches

**Bolt Offset Distance:**

0.240 inches

**Special Features:**

Buttons-material 2024-t3, 2024-t351, 2024-t4 per qq-a-250/4 or qq-a-225/6, finish anodize per mil-a-8625 typeii, gasket-material synthetic rubber per ams 3240 (40 shore)

**Material:**

Steel comp 631 spring

**Material Specification:**

Mil-s-5059 military specification 1st material response mounting bracket or mil-s-25043 military specification 1st material response mounting bracket or ams5673 assn standard 2nd material response mounting bracket

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spring

**Style Designator:**

Button actuator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A10600

**Mil-std (military Standard):**

Mil-s-5059 spec.